



## **COMMAX.Co.,Ltd.**

- #513-11, Sangdaewon-dong, Jungwon-gu, Sungnam-city, Kyunggi-do, Korea
- TEL. +82-31-7393-540~550 FAX. +82-31-745-2133 [www.commax.com](http://www.commax.com)



# Product Guide

2012

2013  
COMMAX GUIDE

- HOME MOBILE • HOME NETWORK SYSTEM • HOME SECURITY SYSTEM
- HOME AUTOMATION SYSTEM • GATE VIEW SYSTEM
- MULTI ENTRY SYSTEM • SMART VIEW SERIES
- FINE VIEW • DOORPHONE • INTERPHONE
- INTERCOM & WIRELESS INTERCOM
- NURSE CALL SYSTEM • CAMERA
- SMART SECURITY SYSTEM





IF design award  
which is the most  
important international  
product design award  
along with the red dot  
design award and IDEA  
design award.



The GD Selection, by recognizing and rewarding  
excellently designed products, promotes  
the advancement of design and encourages  
innovation and creativity.

# Smart Life, Designed by **COMMAX**

## Contents

- |                          |                      |                                |                         |
|--------------------------|----------------------|--------------------------------|-------------------------|
| ■ HOME MOBILE            | ■ GATE VIEW SYSTEM   | ■ DOORPHONE                    | ■ CAMERA                |
| ■ HOME NETWORK SYSTEM    | ■ MULTI ENTRY SYSTEM | ■ INTERPHONE                   | ■ SMART SECURITY SYSTEM |
| ■ HOME SECURITY SYSTEM   | ■ SMART VIEW SERIES  | ■ INTERCOM & WIRELESS INTERCOM |                         |
| ■ HOME AUTOMATION SYSTEM | ■ FINE VIEW          | ■ NURSE CALL SYSTEM            |                         |



## SMART CONTROL

Smart Home Technology of commax offers the smart life style eliminating the need to walk from room to room to adjust lights, temperatures, curtains and audio / video communication, It's always at your fingertips.

## SMART SECURITY

COMMAX Security System takes the responsibility for safety. It keeps you in safe inside and outside of your house such as in off-limits of household entrance, saving visitor's image during your absence, trespassing detection etc.

## SMART CONTENTS

A variety of delights enjoying the latest music, film and so on through the internet access, and UCC, game can be experienced in real time everywhere with WiFi connection enabled.





# HOME NETWORK SYSTEM

Internet enabled full touch screen operable device offers a full fledged features of home automation with modern aesthetic design authorized by IF design award. Pebble is design motif to make you feel comfortable just like at beach. Various colors are available (Silver, Dark, Gold) on 1020A.



## 2012 New Product

### CDP-1020P



- Full touch screen operable
- Modern aesthetic design winning IF design award putting pebbles into product.
- Visitor image monitoring, conversation • Security • GUI
- Home control function • Scene setting
- Reservation function • Convenient function
- Entertainment function • Home away control

|              |  |
|--------------|--|
| Power source | DC 14.5V, 2.5A   |
| Mounted type | Flush-mounted type   |
| LCD size     | 10.1" color TFT LCD  |
| Dimension    | 318 X 215 X 18(61)(mm)   |
| Operation    | MPEG-4/H.264 video support(Video format depends on products) / SIP standard protocol |
| Image Saving | 128 cuts   |
| Reception    | Individual Entrance : 50m(0.65φ)   |
| Distance     | LAN session : 100m(from switching hub)   |

### Recommended Products (Lobby phone)

### DRC-700S (Crystal Lobby phone)



- Registering up to 3 RF-ID cards per each household
- Crystal Window
- Guard Call and Talk
- House call by household number

|              |  |
|--------------|--|
| Power source | DC 14V, 2.5A                           |
| Mounted type | Flush-mounted type                     |
| RFID Card    | 13.56Mhz                               |
| Wiring       | UTP(CAT, 5e)                           |
| Dimension    | 240 X 270 X 13(40)(mm)                 |
| Distance     | LAN session : 100m(from switching hub) |
| Rain Shield  | 250 X 275 X 73(mm)                     |
|              | Alluminum Diecasting                   |
|              | Flush-mounted type /                   |
|              | Wall surface mounted type              |



## WALL PAD

### CDP-1020A



- iF Design Award & Aluminium panel • Touch GUI
- Monitoring • Talk with a visitor
- Monitoring a visitor at individual camera
- Talk between households • Telephone function
- Monitoring image of a visitor when being away
- Door lock release • Security • All-put out lights
- Additional to subphone

|              |                        |
|--------------|------------------------|
| Power source | DC 14.5V, 2.5A         |
| Mounted type | Flush-mounted type     |
| LCD size     | 10.1", wide color LCD  |
| Wiring       | LAN(CAT, 5e)           |
| Image Saving | 128 cuts               |
| Dimension    | 318 X 215 X 18(61)(mm) |

# HOME MOBILE

## 2012 New Product

### COMMAX Home Mobile

### CHM-890B



- A8 Coretex 1GHz • Android 2.3
- 16GB Movi-NAND/ 512MB RAM
- Wi-Fi / Bluetooth / GPS • USB , DC, EarMic Jack
- Option : UART, Audio out, HDMI

|         |   |
|---------|---|
| Battery | 6,000mAh Li-polymer Battery<br>Built-in rechargeable lithium-polymer battery/Up to 5 hrs on movie play<br>Up to 24 hrs on Standby mode                          |
| Audio   | Stereo Speaker inside<br>Microphone inside<br>Dolby 5.1 Channel Sound<br>Movie : DivX, Xvid, H.264, MPEG-4 SP/ASP, H.263, WMV7/8, VC-1/WMV9, AVI, ASF, 3GP, MKV |
| Codec   | Audio : MP2/3, WMA7/8/9, AAC, AAC+, Ogg Vorbis, FLAC, APE, AC-3<br>Viewer : EPUB, JPEG, PNG, BMP, GIF   |
| Camera  | CMOS, 1.3M Pixel Camera   |

### CDP-700P



- Full touch screen operable
- Modern aesthetic design winning IF design award putting pebbles into product.
- Visitor image monitoring, conversation • Security • GUI
- Home control function • Scene setting
- Reservation function • Convenient function
- Entertainment function • Home away control

|              |  |
|--------------|--|
| Power source | DC 14.5V, 2.5A   |
| Mounted type | Flush-mounted type   |
| LCD size     | 7" color TFT LCD   |
| Dimension    | 243 X 168 X 18(61)(mm)   |
| Operation    | MPEG-4/H.264 video support(Video format depends on products) / SIP standard protocol |
| Image Saving | 128 cuts   |
| Reception    | Individual Entrance : 50m(0.65φ)   |
| Distance     | LAN session : 100m(from switching hub)   |

### Recommended Products (Guard Station)

### CDS-70M



- Full touch screen operable
- Calling and talking with household
- Parking management
- Screening for delivery
- Emergency indication and screening inside house

|              |  |
|--------------|--|
| Power source | DC 12V, 1A                             |
| Mounted type | Wall surface mounted type / Desk type  |
| LCD size     | 7" color LCD                           |
| Wiring       | UTP(CAT, 5e)                           |
| Dimension    | 240 X 270 X 13 [40](mm)                |
| Distance     | LAN session : 100m(from switching hub) |



## CDP-700A



- iF Design Award & Aluminium panel • Touch GUI
- Monitoring • Talk with a visitor
- Monitoring a visitor at individual camera
- Talk between households • Telephone function
- Monitoring image of a visitor when being away
- Door lock release • Security • All-put out lights
- Additional to subphone

|              |                        |
|--------------|------------------------|
| Power source | DC 14.5V, 2.5A         |
| Mounted type | Flush-mounted type     |
| LCD size     | 7" wide color LCD      |
| Wiring       | LAN(CAT, 5e)           |
| Image Saving | 128 cuts               |
| Dimension    | 239 X 165 X 18(61)(mm) |

## CDP-1020C



- Charming wall pad • Touch GUI
- Monitoring • Talk with a visitor
- Monitoring a visitor at individual camera
- Talk between households • Telephone function
- Monitoring image of a visitor when being away
- Door lock release • Security
- All-put out lights • Additional to subphone

|              |                        |
|--------------|------------------------|
| Power source | DC 14.5V, 2.5A         |
| Mounted type | Flush-mounted type     |
| LCD size     | 10.1" wide color LCD   |
| Wiring       | LAN(CAT, 5e)           |
| Image Saving | 128 cuts               |
| Dimension    | 318 X 215 X 18(61)(mm) |

## CKV-1020C




- Monitoring & Talk with a visitor
- Watching TV & Listening to radio • Alarm setting
- Time display • Messaging recording
- Telephone receiving
- Speech recognition(Optional)
- Digital Tuner(Optional)
- Door lock release

|              |                             |
|--------------|-----------------------------|
| Power source | AC 100~240V, 50/60Hz        |
| Distance     | To Master unit : 30m( 0.65) |
| LCD size     | 10.1"                       |
| Wiring       | Master unit : 6 wires       |
| Dimension    | 400 x 259 x 212(mm)         |

## SECURITY



## CONTROL



## ECO



### Smart SECURITY



**CCTV**  
Check around the house with CCTV situation



**Call and Save image of visitor**  
Check and save image of visitor in front of lobby gate and front gate

### Smart CONTROL



**Green Energy Solution**  
Solar energy, Stand by power



**Energy management solution**  
Temperature control, AMR

### Smart CONTENTS




U-health Care




Education, E-Book

### System Diagram



### System Diagram





# HOME SECURITY SYSTEM

Internet enabled full touch screen operable devices offer wide range of fail safe security feature with a single touch to your Home.



## 2012 New Product

### DRC-700S (Crystal Lobby phone)



- Registering up to 3 RF-ID cards per each household
- Crystal Window
- Guard Call and Talk
- House call by household number

|              |   |
|--------------|---|
| Power source | DC 14V, 2.5A  |
| Mounted type | Flush-mounted type  |
| RFID Card    | 13.56Mhz  |
| Wiring       | UTP(CAT, 5e)  |
| Dimension    | 240 X 270 X 13(40)(mm)  |
| Rain Shield  | 250 X 275 X 73(mm)<br>Alluminum Diecasting<br>Flush-mounted type /<br>Wall surface mounted type |



### CDS-70M



- Separate wires for Guard connection
- Guard Call and Talk(1 CH)
- House call by household number
- Distance : LAN session : 100m(from switching hub)
- Full touch screen operable
- Android OS
- Calling and talking with household
- Parking management
- Screening for delivery
- Emergency indication and screening inside house

|              |  |
|--------------|--|
| Power source | DC 12V, 1A                             |
| Mounted type | Wall surface mounted type / Desk type  |
| LCD size     | 7" color LCD                           |
| Wiring       | UTP(CAT, 5e)                           |
| Dimension    | 240 X 270 X 13 [40](mm)                |
| Distance     | LAN session : 100m(from switching hub) |

## WALL PAD

### CHS-1020A / CHS-1020AW



- iF Design Award & Aluminium panel • Touch GUI
- Monitoring • Talk with a visitor
- Monitoring a visitor at individual camera
- Talk between households
- Monitoring image of a visitor when being away
- Door lock release • Security • All-put out lights
- Additional to IP subphone

|              | 1020A  | 1020AW |
|--------------|--|--------|
| Power source | DC 14.5V, 2.5A                                 |        |
| Mounted type | Flush-mounted type   Wall surface mounted type |        |
| LCD size     | 10.1" wide color LCD                           |        |
| Wiring       | LAN(CAT, 5e)                                   |        |
| Dimension    | 318 X 215 X 18(61)(mm)                         |        |

### CHS-700A / 700AW



- iF Design Award & Aluminium panel • Touch GUI
- Monitoring • Talk with a visitor
- Monitoring a visitor at individual camera
- Talk between households
- Monitoring image of a visitor when being away
- Door lock release • Security • All-put out lights
- Additional to IP subphone


|              | 700A   | 700AW |
|--------------|--|-------|
| Power source | DC 14.5V, 2.5A                                 |       |
| Mounted type | Flush-mounted type   Wall surface mounted type |       |
| LCD size     | 7" wide color LCD                              |       |
| Wiring       | LAN(CAT, 5e)                                   |       |
| Dimension    | 239 X 165 X 18(61)(mm)                         |       |

### CHS-1020C



- Charming wall pad • Touch GUI
- Monitoring • Talk with a visitor
- Monitoring a visitor at individual camera
- Talk between households
- Monitoring image of a visitor when being away
- Door lock release • Security
- All-put out lights

|              |                        |
|--------------|------------------------|
| Power source | DC 14.5V, 2.5A         |
| Mounted type | Flush-mounted type     |
| LCD size     | 10.1" wide color LCD   |
| Wiring       | LAN(CAT, 5e)           |
| Dimension    | 318 X 215 X 18(61)(mm) |






## System Diagram

### Specialized for Security feature

- Interactive with smart phone
- CCTV monitoring
- SMS/TEXT message in monitor
- Interface with sensor device
- **Max. House hold connection depending on server capacity**

#### System Diagram

|       |         |
|-------|---------|
| — L — | LAN     |
| — 2 — | 2 Wires |
| — 3 — | 3 Wires |
| — 4 — | 4 Wires |
| — 6 — | 6 Wires |





# HOME AUTOMATION SYSTEM

- Customization of Operating Parameters • Monitoring a visitor at individual camera
- Unlimited Households • Total Security Management
- Talk between households • Talk with a visitor • Security



## 2012 New Product

### Premium Wall-pad

#### CAV-700P



- **Touch GUI**
- Monitoring • Talk with a visitor
- Monitoring a visitor at individual camera
- Talk between households
- Monitoring image of a visitor when being away
- Door lock release
- Security

|              |                                 |
|--------------|---------------------------------|
| Power source | DC 14.5V, 2.5A                  |
| Mounted type | Flush mounted type              |
| LCD size     | 7" wide color LCD               |
| Wiring       | Common 12 wires, Camera 4 wires |
| Dimension    | 243 X 168 X 18(61)(mm)          |

## 2012 New Product

### Video Door Phone

#### CAV-35FMH



- Monitoring • Talk with a visitor
- Monitoring a visitor at individual camera
- Talk between households
- Monitoring image of a visitor when being away
- Door lock release

|              |                                 |
|--------------|---------------------------------|
| Power source | AC 100~240V, 50/60Hz            |
| Mounted type | Flush mounted type              |
| LCD size     | 3.5" color LCD                  |
| Image Saving | 128 cuts                        |
| Wiring       | Common 12 wires, Camera 4 wires |
| Dimension    | 239 X 165 X 18(61)(mm)          |

## 2012 New Product

### Lobby Phone

#### DRC-700LC / RF 1 (Crystal Lobby phone)



- Registering up to 3 RF cards per each household
- Crystal Window
- Separate wires for Guard connection
- Guard Call and Talk (3 CH)
- House call by household number
- Distance : Max. 300 Meter (Coaxial 5C2V)

|              |                                      |
|--------------|--------------------------------------|
| Power source | DC 12V, 1A                           |
| Mounted type | Flush-mounted type                   |
| RFID Card    | 13.56Mhz (Optional RF function)      |
| Wiring       | Common 10 wires + 5C2V Coaxial Cable |
| Dimension    | 240 X 270 X 13(40)(mm)               |
| Rain Shield  | 250 X 275 X 73(mm)                   |
|              | Alluminum Diecasting                 |
|              | Flush-mounted type /                 |
|              | Wall surface mounted type            |



## HOME AUTOMATION SYSTEM

#### CAV-707AM / 707AM1 / 707AM2



- Touch GUI • Compatible with 1.8GHz wireless telephone
- Monitoring • Talk with a visitor
- Monitoring a visitor at individual camera
- Talk between households • Telephone function
- Monitoring image of a visitor when being away
- Door lock release • Security • All-put out lights
- Additional to subphone

|              |                                 |
|--------------|---------------------------------|
| Power source | DC 14.5V, 2.5A                  |
| Mounted type | Flush mounted type              |
| LCD size     | 7" wide color LCD               |
| Wiring       | Common 12 wires, Camera 4 wires |
| Dimension    | 239 X 165 X 18(61)(mm)          |

#### CAV-51SD



- Monitoring • Talk with a visitor
- Monitoring a visitor at individual camera
- Talk between households • Telephone function
- Door lock release • Security • Handset

|              |                                 |
|--------------|---------------------------------|
| Power source | AC 100~240V, 50/60Hz            |
| Mounted type | Wall surface mounted type       |
| LCD size     | 5" color LCD                    |
| Wiring       | Common 12 wires, Camera 4 wires |
| Dimension    | 323 X 165 X 56(mm)              |

Recommended Products (Guard Station)

#### CDS-MV





## System Diagram

### CAV-501D



- Monitoring
- Talk with a visitor
- Monitoring a visitor at individual camera
- Talk between house holds / DID
- Telephone function
- Door lock release
- Security

|              |                                 |
|--------------|---------------------------------|
| Power source | AC 100~240V, 50/60Hz            |
| Mounted type | Flush mounted type              |
| LCD size     | 5" color LCD                    |
| Wiring       | Common 12 wires, Camera 4 wires |
| Dimension    | 263 X 220 X 23(82)(mm)          |

### AP-481LN




- Talk with a visitor
- Talk between house holds
- Door lock release
- Handset

|              |                                     |
|--------------|-------------------------------------|
| Power source | AC 110/220/230V, 50/60Hz            |
| Mounted type | Wall surface mounted type           |
| Wiring       | Common 10 wires, Individual 3 wires |
| Dimension    | 195 X 135 X 50(mm)                  |

- Calling and talking with household
- Parking management (option)
- Intercommunication between household
- Home delivery notice
- Emergency indication and screening inside house

|              |  |
|--------------|--|
| Power source | DC 15V, 1.5A                                     |
| LCD size     | 5" color LCD                                     |
| Wiring       | Master unit 8 wires / 5C2V Coaxial Cable(option) |
| Dimension    | 233 X 223 X 100(mm)                              |



## System Diagram

|  |               |
|--|---------------|
|  | Coaxial Cable |
|  | 2 Wires       |
|  | 4 Wires       |
|  | 8 Wires       |



# GATE VIEW SYSTEM

- Easy Installation 1 Cable system (UTP Cable) • Connectable individual Camera
- Guard Call and Door release (Lobby & Door camera) • OSD Menu • Up to 400 households
- Guard Station Talk • Lobby phone Talk • Door lock release



## 2012 New Product

### Premium Video Door Phone

#### CAV-70PG / CAV-70PGM



- LED Back Light • Talk with a visitor • Door lock release
- No Coaxial Cable required for Video • OSD Menu
- Monitoring a visitor at Individual camera
- Guard Station Talk • Lobby phone Talk
- Guard Call and Door release (Lobby & Door camera)
- Built-in Image Memory (Micro SD Card optional): CAV-70PGM

|              | 70PG  | 70PGM (Memory) |
|--------------|---|----------------|
| Power source | AC 100~240V, 50/60Hz                        |                |
| Mounted type | Wall surface mounted type                   |                |
| LCD size     | 7" wide color LCD                           |                |
| Image Saving | 128 cuts & Video Clip                       |                |
| Wiring       | UTP (CAT. 5e) (Common 8wires+Camera 4wires) |                |
| Dimension    | 243 X 168 X 18(61)(mm)                      |                |

#### CAV-40QG / 40QGD / 40QGM



- LED Back Light • Talk with a visitor • Door lock release
- No Coaxial Cable required for Video • OSD Menu
- Monitoring a visitor at Individual camera
- Guard Station Talk • Lobby phone Talk
- Guard Call and Door release (Lobby & Door camera)
- Built-in Image Memory (Micro SD Card optional): CAV-40QGM

|              | 40QG  | 40QGM (Memory) | 40QGD  |
|--------------|---|----------------|--------|
| Power source | AC 100~240V, 50/60Hz                        |                | DC 18V |
| Mounted type | Wall surface mounted type                   |                |        |
| LCD size     | 4" color LCD                                |                |        |
| Image Saving | 128 cuts & Video Clip                       |                |        |
| Wiring       | UTP (CAT. 5e) (Common 8wires+Camera 4wires) |                |        |
| Dimension    | 235 X 140 X 35(mm)                          |                |        |

#### CAV-40NG / 40NGM



- LED Back Light • Talk with a visitor • Door lock release
- No Coaxial Cable required for Video • OSD Menu
- Monitoring a visitor at Individual camera
- Guard Station Talk • Lobby phone Talk
- Guard Call and Door release (Lobby & Door camera)
- Built-in Image Memory (Micro SD Card optional): CAV-40NGM

|              | 40NG  | 40NGM (Memory) |
|--------------|---|----------------|
| Power source | AC 100~240V, 50/60Hz                        |                |
| Mounted type | Wall surface mounted type                   |                |
| LCD size     | 4" color LCD                                |                |
| Image Saving | 128 cuts & Video Clip                       |                |
| Wiring       | UTP (CAT. 5e) (Common 8wires+Camera 4wires) |                |
| Dimension    | 249 X 122 X 38(mm)                          |                |

## 2012 New Product

### Lobby Phone

#### DRC-700LGC



- Crystal Window • House call by household

|              |                                 |
|--------------|---------------------------------|
| Power source | DC 12V, 1A                      |
| Mounted type | Flush-mounted type              |
| RFID Card    | 13.56Mhz (Optional RF function) |
| Wiring       | UTP (CAT. 5e)                   |
| Dimension    | 240 X 270 X 13 [40] (mm)        |
| Rain Shield  | 250 X 275 X 73(mm)              |

- Aluminum Diecasting
- Flush-mounted type
- Wall surface mounted type



#### DRC-900LVC

(Vandal Proof Lobby Pinhole Camera)



- Separate wires for Guard connection
- Guard Call and Talk • Alluminum Diecasting • Distance: Max.300(M)

|              |                                 |
|--------------|---------------------------------|
| Power source | DC 12V, 1A                      |
| Mounted type | Wall surface mounted type       |
| RFID Card    | 13.56Mhz (Optional RF function) |
| Wiring       | UTP(CAT. 5e)                    |
| Dimension    | 130 X 240 X 13 [40](mm)         |
| Rain Shield  | 250X275X73(mm)                  |

- Alluminum Diecasting
- Flush-mounted type



#### DRC-GAC



- Max. 4 Lobby Panels connectable
- House call by household number

|              |                                 |
|--------------|---------------------------------|
| Power source | DC 12V, 1A                      |
| Mounted type | Flush mounted type              |
| RFID Card    | 13.56Mhz (Optional RF function) |
| Wiring       | UTP(CAT. 5e)                    |
| Dimension    | 123 X 314 X 50(mm)              |

## GATE VIEW SYSTEM

#### CAV-70GA



- LED Back Light • OSD Menu • Talk with a visitor
- No Coaxial Cable required for Video • Guard Station Talk
- Lobby phone Talk • Door lock release
- Guard Call and Door release (Lobby & Door camera)
- Monitoring a visitor at Individual camera

|              |   |
|--------------|---|
| Power source | AC 100~240V, 50/60Hz                        |
| Mounted type | Wall surface mounted type                   |
| LCD size     | 7" color LCD                                |
| Wiring       | UTP (CAT. 5e) (Common 8wires+Camera 4wires) |
| Dimension    | 243 X 168 X 35(mm)                          |

#### CAV-35GN



- LED Back Light • Talk with a visitor • No Coaxial Cable required for Video • Monitoring a visitor at Individual camera
- Guard Station Talk • Lobby phone Talk • Door lock release
- Guard Call and Door release (Lobby & Door camera)

|              |   |
|--------------|---|
| Power source | AC 100~220V, 50/60Hz                        |
| Mounted type | Wall surface mounted type                   |
| LCD size     | 3.5" color LCD                              |
| Wiring       | UTP (CAT. 5e) (Common 8wires+Camera 4wires) |
| Dimension    | 192 X 209 X 31(mm)                          |

### Recommended Products (Guard Station)

#### CDS-4GS



- Interphone with In-house unit • Interphone with Lobby phone
- Door release for Lobby door

|              |                                   |
|--------------|-----------------------------------|
| Power source | DC 12V, 1A                        |
| Mounted type | Wall surface mounted & Table type |
| Wiring       | UTP (CAT. 5e) (4wires)            |
| Dimension    | 195 X 135 X 50(mm)                |



### CAV-50GN



- LED Back Light • Talk with a visitor • No Coaxial Cable required for Video • Monitoring a visitor at Individual camera
- Guard Station Talk • Lobby phone Talk
- Guard Call and Door release (Lobby & Door camera)
- Door lock release

|              |   |
|--------------|---|
| Power source | AC 100~240V, 50/60Hz                        |
| Mounted type | Wall surface mounted type                   |
| LCD size     | 5" color LCD                                |
| Wiring       | UTP (CAT. 5e) (Common 8wires+Camera 4wires) |
| Dimension    | 259 X 126 X 37(mm)                          |

### CAV-50GA



- LED Back Light • Talk with a visitor • No Coaxial Cable required for Video • Monitoring a visitor at Individual camera
- Guard Station Talk • Lobby phone Talk
- Guard Call and Door release (Lobby & Door camera)
- Door lock release

|              |   |
|--------------|---|
| Power source | AC 100~240V, 50/60Hz                        |
| Mounted type | Wall surface mounted type                   |
| LCD size     | 5" color LCD                                |
| Wiring       | UTP (CAT. 5e) (Common 8wires+Camera 4wires) |
| Dimension    | 245 X 175 X 45(mm)                          |

### CAV-35GH



- LED Back Light • Talk with a visitor • No Coaxial Cable required for Video • Monitoring a visitor at Individual camera
- Guard Station Talk • Lobby phone Talk
- Guard Call and Door release (Lobby & Door camera)
- Door lock release • OSD Menu

|              |   |
|--------------|---|
| Power source | AC 100~240V, 50/60Hz                        |
| Mounted type | Wall surface mounted type                   |
| LCD size     | 3.5" color LCD                              |
| Wiring       | UTP (CAT. 5e) (Common 8wires+Camera 4wires) |
| Dimension    | 133 X 209 X 31(mm)                          |

### AP-3SG



- Talk with a visitor • Guard Station Talk
- Lobby phone Talk • Door lock release

|              |  |
|--------------|--|
| Power source | AC 100V, 110V, 220V, 50/60Hz                   |
| Mounted type | Wall surface mounted type                      |
| Wiring       | UTP (CAT. 5e) (Common 6wires+Door unit 3wires) |
| Dimension    | 94 X 185 X 38(mm)                              |

### Video Signal Distributor


#### VD-103



- Coverage of House hold
  - Covering up to 200 Flats (Max,300m) with out Video signal distributor
  - Covering up to 400 Flats (Max,300m) with Video signal distributor

2. 1 INPUT & 3 OUTPUT

### System Diagram





# MULTI ENTRY SYSTEM

- Easy Installation 1 Cable system (UTP Cable)
- Up to 2,400 Households • In-house unit from audio to video • Door lock release(Lobby phone)
- Additional 2 subunits connectable • Sub-monitors need an extra power source



## MULTI ENTRY SYSTEM

### CAV-51AM



- Additional 2 subunits connectable
- Sub-monitors need an extra power source (DC 24~28V)
- Door lock release

|              |                           |
|--------------|---------------------------|
| Power source | from CCU-FS               |
| Mounted type | Wall surface mounted type |
| LCD size     | 5" color LCD              |
| Wiring       | 6 wires                   |
| Dimension    | 245 X 175 X 45(mm)        |

### CAV-51M



- Additional 2 subunits connectable
- Sub-monitors need an extra power source (DC 24~28V)
- Door lock release

|              |                           |
|--------------|---------------------------|
| Power source | from CCU-FS               |
| Mounted type | Wall surface mounted type |
| LCD size     | 5" color LCD              |
| Wiring       | 6 wires                   |
| Dimension    | 245 X 175 X 45(mm)        |

### CAV-35NM



- Additional 2 subunits connectable
- Sub-monitors need an extra power source (DC 24~28V)
- Door lock release

|              |                           |
|--------------|---------------------------|
| Power source | from CCU-FS               |
| Mounted type | Wall surface mounted type |
| LCD size     | 3.5" color LCD            |
| Wiring       | 6wires                    |
| Dimension    | 192 X 209 X 31(mm)        |

### CAV-35HM



- Additional 2 subunits connectable
- Sub-monitors need an extra power source (DC 24~28V)
- Door lock release

|              |                           |
|--------------|---------------------------|
| Power source | from CCU-FS               |
| Mounted type | Wall surface mounted type |
| LCD size     | 3.5" color LCD            |
| Wiring       | 6 wires                   |
| Dimension    | 133 X 209 X 31(mm)        |

### CDS-2MG



- Talk with household
- Talk with common entrance
- Door lock release

|              |   |
|--------------|---|
| Power source | from CCU-BS   |
| Mounted type | Wall surface mounted type or Desk Top                 |
| Wiring       | 2 wires   |
| Dimension    | 195 X 135 X 50(mm) /<br>Hand set : 196 X 200 X 50(mm) |

### AP-5HM




- Additional 2 subunits connectable • Door lock release
- Talk with a visitor • No need for additional power source

|              |                           |
|--------------|---------------------------|
| Power source | from CCU-FS               |
| Mounted type | Wall surface mounted type |
| Wiring       | 5 wires                   |
| Dimension    | 94 X 259 X 55(mm)         |

## DISTRIBUTORS

### Outside distributor

#### CCU-OS



|              |   |
|--------------|---|
| Power source | AC 100~220V, 50/60Hz  |
| Wiring       | 1)CCU-OS to CCU-BS : 8 wires<br>2)CCU-OS to DRC-OSC/OSB : 8 wires                           |
| Dimension    | 300 X 200 X 52(mm)  |
| Distance     | 1)CCU-BS to CCU-OS : 400m<br>2)Wiring can be used with one UTP cable(CAT 5) to entry panel. |

### Floor distributor

#### CCU-FS



|              |   |
|--------------|---|
| Power source | DC 24~28V, 5A   |
| Wiring       | CCU-FS to in-house  |
| Dimension    | unit : 6 wires  |
| Distance     | 159 X 88 X 59(mm)   |
|              | 1)CCU-BS to last CCU-FS : 200m<br>2)Wiring can be used with one UTP cable (CAT 5) to entry panel. |

### Building distributor

#### CCU-BS



|              |   |
|--------------|---|
| Power source | DC 24~28V, 5A   |
| Wiring       | CCU-BS to CCU-FS : 8 wires  |
| Dimension    | 159 X 88 X 59(mm)   |
| Distance     | 1)CCU-BS to last CCU-FS : 200m / CCU-BS to entry panel, within 20m on normal power operation (Using separate power supply maximum of up to 100m)<br>2)Wiring can be used with one UTP cable (CAT 5) to entry panel. |



#### Recommended Products (Lobby phone)

##### DRC-OSC

- Connect up to 4 multi-entry
- Door release by personal identity number
- Talk with guard

##### DRC-MSC

- Connect up to 4 multi-entry
- Door release by personal identity number
- Talk with guard
- Connect all multi-entry panels with main distributor (CCU-BS)

##### DRC-nSC

- Connect up to 4 multi-entry panel per building
- Connect all multi-entry panels with main distributor (CCU-BS)

##### DR-nSB

- Connect up to 4 multi-entry panel per building
- Connect all multi-entry panels with main distributor (CCU-BS)


|              |                                       |
|--------------|---------------------------------------|
| Power source | OSC (from CCU-OS) / MSC (from CCU-BS) |
| Mounted type | Flush mounted type                    |
| Wiring       | 8 wires                               |
| Dimension    | 140 X 341 X 30(44) (mm)               |

|              |                         |
|--------------|-------------------------|
| Power source | from CCU-BS             |
| Mounted type | Flush mounted type      |
| Wiring       | 8 wires                 |
| Dimension    | 140 X 341 X 30(44) (mm) |

|              |                         |
|--------------|-------------------------|
| Power source | from CCU-BS             |
| Mounted type | Flush mounted type      |
| Wiring       | 8 wires                 |
| Dimension    | 140 X 341 X 30(44) (mm) |

#### System Diagram

##### 1 Cable System (UTP Cable)





# SMART VIEW SERIES

## SMART VIEW - X

### CDV-72BXM / BXS



- Connectable 4 dect-phones(option)
- Door lock release & talk with a visitor
- Intercommunication

|              |   |
|--------------|---|
| Power source | DC 14V, 3A                              |
| Mounted type | Wall surface Mounted type               |
| LCD size     | 7" wide color LCD                       |
| Wiring       | 4 wire to Camera / 6 wire to interphone |
| Dimension    | 314 X 173 X 44(mm)                      |
| Distance     | 50m                                     |

### CDS-SDX



- Built-in 4-channel full D1 real-time stand alone DVR • Triplex • H.264 H/W Codec
- Event call • Network monitoring via web site

|                       |                    |
|-----------------------|--------------------|
| Power source          | DC 12V             |
| Wiring                | 4wires             |
| Dimension             | 300 X 200 X 51(mm) |
| Video / Audio         | 4/1                |
| Monitoring, Recording | 120 / 100          |

### SENSOR



CIS-30M

- DC 10.8~25V
- 73 X 177 X 84(mm)
- Outdoor, Indoor



CIS-10M

- DC 10.8~25V
- 73 X 177 X 84(mm)
- Outdoor, Indoor



CPS-200P

- DC 8~14V
- 55 X 13 X 12(mm)
- Indoor



CPS-100D

- DC 8~18V
- 131 X 60(mm)
- Indoor



MS-10

- 0.5A
- 65 X 14 X 14(mm)
- Inside of door



### CCTV & DVR

- Up to 4 CCTV cameras
- Real time recoding (CCTV camera) & playback
- H.264 Compression
- Monitors show and DVR record the scene of CCTV camera when sensor is activated

### ALARM

- 4 security zone by sensors & Alert to the designated phone


### Door Access

- Up to 2 door cameras • Door release • Door Access
- Monitoring & talk with a visitor • CCTV Camera
- Total Security & communication System
- Network • Alarm Sensor • DVR


### System Diagram

#### System Diagram

|  |               |
|--|---------------|
|  | Coaxial Cable |
|  | 2 Wires       |
|  | 4 Wires       |
|  | 6 Wires       |



## System Diagram



## SMART VIEW (Wide Quad)


### CDV-1020AQ



- iF Design Award & Aluminium panel
- Wide Quad screen display • Visitor image memory(68 cuts)
- User friendly GUI & Touch screen display
- Connectable 4 dect-phones & 4 Cameras
- Door lock release & talk with a visitor • Intercommunication

|              |                               |
|--------------|-------------------------------|
| Power source | AC 100V~240V, 50/60Hz, 25W    |
| Mounted type | Wall surface Mounted type     |
| LCD size     | 10.1" wide color LCD with GUI |
| Wiring       | 4wire to Camera               |
| Dimension    | 318 X 215 X 18(61)(mm)        |
| Distance     | 50m to Camera                 |
| Image record | NTSC : 68cuts / PAL : 58cuts  |

## System Diagram



## SMART VIEW (Quad)


### CDV-71BQ / CDV-71BQS



- Quad screen display • Expandable up to 2 monitors
- Connectable up to 4 cameras
- Visitor image memory(NTSC : 68 cuts, PAL : 58 cuts)
- Door answering & monitoring • Door release

|              |   |
|--------------|---|
| Power source | AC 100V~240V, 50/60Hz, 25W                                      |
| Mounted type | Wall surface Mounted type                                       |
| LCD size     | 7" wide color LCD   |
| Wiring       | Camera to CDV-71BQ : 4 wires<br>CDV-71BQ to CDV-71BQS : 6 wires |
| Dimension    | 314 X 173 X 53(mm)  |

## System Diagram



## SMART VIEW (World first)

### CAV-71B / 72B



- Room to room call & Pause (Expandable up to 20 monitors)
- Handset & hands-free • Door answering & monitoring
- Connectable up to 4 cameras • OSD interface
- Visitor image memory(128 cuts) • Security : Burglar
- CCTV surveillance camera • Dect phone up to 4(CAV-72B)

|                        |   |
|------------------------|---|
| Power source           | AC 100V~240V, 50/60Hz, 25W  |
| Mounted type           | Wall surface Mounted type   |
| LCD size               | 7" wide color LCD   |
| Wiring                 | Camera to central unit : 4 wires<br>Central unit to CAV-72B : 6 wires<br>CAV-72B to CAV-71B : 6 wires |
| Dimension              | 314 X 173 X 53(mm)  |
| Central Unit (CDS-4CM) |   |
| Dect phone             |   |



# FINE VIEW

IF Award winner, the world best seller, COMMAX is the delivering simply the best to you.

- Fine view Display
- 3.5", 4", 5", 7" monitor available



## 2012 New Product

## Premium Video Door Phone


### CDV-70PM



- PAL, NTSC Convertable • LED Back Light • Hands free
- Talk with a visitor • Monitoring an entrance
- Interphone function (DP-4VHP) • Door lock release
- Up to 2 cameras, 2 CCTV cameras and 1 interphone
- Built-in Image Memory (Micro SD Card optional)

|              |  |
|--------------|--|
| Power source | AC 100~240V, 50/ 60Hz  |
| Mounted type | Wall surface mounted type  |
| LCD size     | 7" wide color LCD  |
| Image Saving | 128 cuts & Video Clip  |
| Wiring       | Individual camera 4wires, CCTV camera 2wires, Interphone 4 wires |
| Dimension    | 243 X 168 X 35(mm)   |

### CDV-70P



- PAL, NTSC Convertable • LED Back Light
- Talk with a visitor • Monitoring an entrance • Hands free
- Interphone function (DP-4VHP) • Door lock release
- Up to 2 cameras, 2 monitors and 2 interphones

|              |                           |
|--------------|---------------------------|
| Power source | AC 100~240V, 50/ 60Hz     |
| Mounted type | Wall surface mounted type |
| LCD size     | 7" wide color LCD         |
| Wiring       | 4 wires                   |
| Dimension    | 243 X 168 X 35(mm)        |

### CDV-40QM



- PAL, NTSC Convertable • LED Back Light • Hands free
- Talk with a visitor • Monitoring an entrance
- Interphone function (DP-4VHP) • Door lock release
- Up to 2 cameras, 2 CCTV cameras and 1 interphone
- Built-in Image Memory (Micro SD Card optional)

|              |  |
|--------------|--|
| Power source | AC 100~240V, 50/ 60Hz  |
| Mounted type | Wall surface mounted type  |
| LCD size     | 4" color LCD   |
| Image Saving | 128 cuts & Video Clip  |
| Wiring       | Individual camera 4wires, CCTV camera 2wires, Interphone 4 wires |
| Dimension    | 235 X 140 X 35(mm)   |

### CDV-40Q



- PAL, NTSC Convertable • LED Back Light
- Talk with a visitor • Monitoring an entrance • Hands free
- Interphone function (DP-4VHP) • Door lock release
- Up to 2 cameras, 2 monitors and 2 interphones

|              |                           |
|--------------|---------------------------|
| Power source | AC 100~240V, 50/ 60Hz     |
| Mounted type | Wall surface mounted type |
| LCD size     | 4" color LCD              |
| Wiring       | 4 wires                   |
| Dimension    | 235 X 140 X 35(mm)        |

### CDV-40NM



- PAL, NTSC Convertable • LED Back Light • Talk with a visitor
- Monitoring an entrance • Interphone function (DP-4VHP)
- Door lock release • Up to 2 cameras, 2 CCTV cameras and 1 interphone • Built-in Image Memory (Micro SD Card optional)

|              |  |
|--------------|--|
| Power source | AC 100~240V, 50/ 60Hz  |
| Mounted type | Wall surface mounted type  |
| LCD size     | 4" color LCD   |
| Image Saving | 128 cuts & Video Clip  |
| Wiring       | Individual camera 4wires, CCTV camera 2wires, Interphone 4 wires |
| Dimension    | 249 X 122 X 38(mm)   |

### CDV-40N



- PAL, NTSC Convertable • LED Back Light
- Talk with a visitor • Monitoring an entrance
- Interphone function (DP-4VHP) • Door lock release
- Up to 2 cameras, 2 monitors and 2 interphones

|              |                           |
|--------------|---------------------------|
| Power source | AC 100~240V, 50/ 60Hz     |
| Mounted type | Wall surface mounted type |
| LCD size     | 4" color LCD              |
| Wiring       | 4 wires                   |
| Dimension    | 235 X 140 X 35(mm)        |

## FINE VIEW

### CDV-1020AE



- PAL, NTSC Convertable • PIP(Picture in picture)
- Touch Screen • LED Back Light • Talk with a visitor
- Built in image memory 128 cuts • Monitoring an entrance
- Up to 2 CCTV cameras, 2 cameras, 2 monitors and 2 interphones • GUI

|              |                           |
|--------------|---------------------------|
| Power source | AC 100~240V, 50/ 60Hz     |
| Mounted type | Wall surface mounted type |
| LCD size     | 10.1" color LCD           |
| Wiring       | 4 wires                   |
| Dimension    | 318 X 215 X 53(mm)        |

### CDV-50N



- PAL, NTSC Convertable • LED Back Light • Talk with a visitor
- Crystal-clear video image quality • Monitoring an entrance
- Up to 2 cameras, 2 monitors and 2 interphones
- Interphone function(DP-4VHP) • Door lock release

|              |                           |
|--------------|---------------------------|
| Power source | AC 100~240V, 50/ 60Hz     |
| Mounted type | Wall surface mounted type |
| LCD size     | 5" color LCD              |
| Wiring       | 4 wires                   |
| Dimension    | 259 X 126 X 37(mm)        |

### CDV-35HM



- PAL, NTSC Convertable • LED Back Light • Up to 2 cameras, 2 monitors and 2 interphones • Monitoring an entrance
- Talk with a visitor • Interphone function(DP-4VHP) • Hands free
- Door lock release • Visitor image memory(128 cuts) • Video clip

|              |                           |
|--------------|---------------------------|
| Power source | AC 100~240V, 50/ 60Hz     |
| Mounted type | Wall surface mounted type |
| LCD size     | 3.5" color LCD            |
| Wiring       | 4 wires                   |
| Dimension    | 133 X 209 X 31(mm)        |



### CDV-71AM



- PAL, NTSC Convertable • PIP(Picture in picture) • GUI
- LED Back Light • Built in image memory 128 cut
- Up to 2 CCTV cameras, 2 cameras, 2 monitors and 2 interphones
- Monitoring an entrance • Talk with a visitor
- Interphone function(DP-4VHP)

|              |                           |
|--------------|---------------------------|
| Power source | AC 100~240V, 50/ 60Hz     |
| Mounted type | Wall surface mounted type |
| LCD size     | 7" wide color LCD         |
| Wiring       | 4 wires                   |
| Dimension    | 243 X 168 X 35(mm)        |

### CDV-70A



- PAL, NTSC Convertable • LED Back Light
- Up to 2 cameras, 2 monitors and 2 interphones
- Monitoring an entrance
- Talk with a visitor
- Interphone function(DP-4VHP)

|              |                           |
|--------------|---------------------------|
| Power source | AC 100~240V, 50/ 60Hz     |
| Mounted type | Wall surface mounted type |
| LCD size     | 7" wide color LCD         |
| Wiring       | 4 wires                   |
| Dimension    | 243 X 168 X 35(mm)        |

### CDV-73BE



- PAL, NTSC Convertable • LED Back Light
- Up to 2 cameras, 2 monitors and 2 interphones
- Monitoring an entrance
- Talk with a visitor

|              |                           |
|--------------|---------------------------|
| Power source | AC 100~240V, 50/ 60Hz     |
| Mounted type | Wall surface mounted type |
| LCD size     | 7" wide color LCD         |
| Wiring       | 4 wires                   |
| Dimension    | 314 X 173 X 53(mm)        |

### CDV-51AM



- PAL, NTSC Convertable • LED Back Light • GUI • Talk with a visitor
- Up to 2 cameras, 2 monitors and 2 interphones
- Monitoring an entrance • Interphone function(DP-4VHP)
- Door lock release • Built in image memory 128 cuts

|              |                           |
|--------------|---------------------------|
| Power source | AC 100~240V, 50/ 60Hz     |
| Mounted type | Wall surface mounted type |
| LCD size     | 5" color LCD              |
| Wiring       | 4 wires                   |
| Dimension    | 245 X 175 X 46(mm)        |

### CDV-50A



- PAL, NTSC Convertable • LED Back Light
- Up to 2 cameras, 2 monitors and 2 interphones
- Monitoring an entrance • Talk with a visitor
- Interphone function(DP-4VHP) • Door lock release

|              |                           |
|--------------|---------------------------|
| Power source | AC 100~240V, 50/ 60Hz     |
| Mounted type | Wall surface mounted type |
| LCD size     | 5" color LCD              |
| Wiring       | 4 wires                   |
| Dimension    | 245 X 175 X 46(mm)        |

### CAV-50T2



- PAL, NTSC Convertable • Telephone • Talk with a visitor
- Monitoring a visitor at individual camera
- Guard station talk(CLS-10 only)
- Up to 2 cameras • DID function • Door lock release

|              |                           |
|--------------|---------------------------|
| Power source | AC 100~240V, 50/ 60Hz     |
| Mounted type | Wall surface mounted type |
| LCD size     | 5" color LCD              |
| Wiring       | 4 wires                   |
| Dimension    | 285 X 140 X 46(mm)        |

### CDV-35H



- PAL, NTSC Convertable • LED Back Light
- Up to 2 cameras, 2 monitors and 2 interphones
- Monitoring an entrance • Talk with a visitor • Interphone function(DP-4VHP) • Door lock release • Hands free

|              |                           |
|--------------|---------------------------|
| Power source | AC 100~240V, 50/ 60Hz     |
| Mounted type | Wall surface mounted type |
| LCD size     | 3.5" color LCD            |
| Wiring       | 4 wires                   |
| Dimension    | 133 X 209 X 31(mm)        |

### CDV-35N



- PAL, NTSC Convertable • LED Back Light
- Up to 2 cameras, 2 monitors and 2 interphones
- Monitoring an entrance • Talk with a visitor
- Interphone function(DP-4VHP) • Door lock release

|              |                           |
|--------------|---------------------------|
| Power source | AC 100~240V, 50/ 60Hz     |
| Mounted type | Wall surface mounted type |
| LCD size     | 3.5" color LCD            |
| Wiring       | 4 wires                   |
| Dimension    | 192 X 195 X 31(mm)        |

### CDV-352HD



Door Unit



DRC-20MC

- Easy installation with 2 wiring method in non-polar
- Connectable up to 2 monitors 2 cameras and 2 interphone
- Vivid color with LED back light
- Interphone extension available DP-4VHP


|              |                           |
|--------------|---------------------------|
| Power source | DC 24V, 1A (RF-2AS)       |
| Mounted type | Wall surface mounted type |
| LCD size     | 3.5" wide color LCD       |
| Wiring       | 2 wires                   |
| Dimension    | 133 X 209 X 31(mm)        |



# DOORPHONE

Global steady seller satisfying customers all over the world.

- Aesthetic modern design • Easy to install
- Factory • Office • Hospital



## 2012 New Product

## Door Phone & Door Unit

### DP-2SR



- Talk with a Visitor • Door lock Release
- Two door Release

|              |                              |
|--------------|------------------------------|
| Power source | AC 100V, 110V, 220V, 50/60Hz |
| Mounted type | Wall surface mounted type    |
| Wiring       | 2 wires                      |
| Dimension    | 94 X 185 X 38 (mm)           |

#### Recommended Products (Door Unit)



DR-2GN



DR-2PN



DR-2K



DR-201A



DR-20S

### DP-S01 (M : S)



- Room to Room Talk • Door lock Release
- Talk with a Visitor • Master, Slave intercom

|              |                              |
|--------------|------------------------------|
| Power source | AC 100V, 110V, 220V, 50/60Hz |
| Mounted type | Wall surface mounted type    |
| Wiring       | 5 wires                      |
| Dimension    | 94 X 185 X 38 (mm)           |

#### Recommended Products (Door Unit)



DR-2GN



DR-2PN



DR-2K



DR-201A



DR-20S

### DP-2SN



- DC type • Talk with a Visitor
- No additional adaptor for door release
- Door lock Release
- Extension terminal board

|              |                           |
|--------------|---------------------------|
| Power source | DC 12V                    |
| Mounted type | Wall surface mounted type |
| Wiring       | 2 wires                   |
| Dimension    | 94 X 185 X 38 (mm)        |

#### Recommended Products (Door Unit)



DR-2GNR



DR-2K



DR-201A



DR-201D

#### Recommended Products (Door Unit)

### DP-MS



- Talk with a Visitor
- Up to 40 house holds
- Door lock Release 2 ADP in one household

|              |                           |
|--------------|---------------------------|
| Power source | DC 12V                    |
| Mounted type | Wall surface mounted type |
| Wiring       | 4 wires                   |
| Dimension    | 94 X 185 X 38 (mm)        |



DR-nKM



DR-nKS



DR-nAM



DR-nAS

## DOORPHONE

### DP-2S



- Door lock Release • Talk with a Visitor
- 5 colors (White, Pear, Gold, Silver, Wine)

|              |                              |
|--------------|------------------------------|
| Power source | AC 100V, 110V, 220V, 50/60Hz |
| Mounted type | Wall surface mounted type    |
| Wiring       | 2 wires                      |
| Dimension    | 94 X 185 X 38 (mm)           |

#### Recommended Products (Door Unit)



DR-2GN



DR-2PN



DR-2K



DR-201A



DR-20S

### DP-SS



- Talk with a Visitor • Door lock Release
- Up to 40 house holds

|              |                           |
|--------------|---------------------------|
| Power source | DC 12V                    |
| Mounted type | Wall surface mounted type |
| Wiring       | 4 wires                   |
| Dimension    | 72 X 215 X 38 (mm)        |

#### Recommended Products (Door Unit)



DR-nKM



DR-nKS



DR-nAM



DR-nAS

# INTERPHONE

Global steady seller satisfying customers all over the world.

- Aesthetic modern design • Easy to install
- Factory • Office • Hospital



## 2012 New Product

## Interphone

### TP-12RM

NEW



- Supporting up to 12 pcs of TP-S (Sub-unit)
- Convenient caller identification by adopting red LED
- Covering total system just through one power installation (RF-24AS, 2F-2AS or RF-2A)
- Calling to each station • LED indication

|              |                           |
|--------------|---------------------------|
| Power source | DC 24V, 500mA             |
| Mounted type | Wall surface mounted type |
| Wiring       | Individual 2 wires        |
| Dimension    | 114 X 216 X 33(mm)        |
| Distance     | 1Km(0,65Φ)                |

### TP-nRC

NEW



- Variable system composition (6 or 12 household) • Calling & paging
- ID setting by DIP Switch
- Effective calling to all units by Paging function • Door lock release(optional)
- Easy identification of which sub-unit is in use by LED indication
- Possible to use door phone by enabling DR-DW2N connection

|              |                           |
|--------------|---------------------------|
| Power source | DC 12V, 200mA (1 unit)    |
| Mounted type | Wall surface mounted type |
| Wiring       | Common 4 wires            |
| Dimension    | 114 X 216 X 33(mm)        |
| Distance     | 500m(0,65Φ)               |

### TP-90RN

NEW



- Calling • Exchanging
- Paging • Speaker phone
- 3 Channel simultaneous communication
- Group call • broadcasting
- Caller ID display on FND display
- Privacy function
- Expandable up to 90 pcs

|              |                           |
|--------------|---------------------------|
| Power source | DC 24V, 120mA (1 unit)    |
| Mounted type | Wall surface mounted type |
| Wiring       | Common 10 wires           |
| Dimension    | 114 X 216 X 33(mm)        |
| Distance     | 1Km(0,65Φ)                |

### TP-nKP



- Variable system composition ( 6 or 10 household)
- Effective calling to all units by Paging function
- Easy identification of which sub-unit is in use by LED indication • Calling & paging • Broadcasting

|              |                                    |
|--------------|------------------------------------|
| Power source | DC 24V, 250mA                      |
| Mounted type | Wall surface mounted type          |
| Wiring       | Common 4 wires + n(number of unit) |
| Dimension    | 98 X 215 X 38(mm)                  |
| Distance     | 100m(0,65Φ)                        |


### TP-1K




- 1:1 intercommunication ( Mutual call) • Calling
- Flexible & Variable installation by adopting 1,5 battery
- Applicable to Hospital, Guard station, office environment

|              |                           |
|--------------|---------------------------|
| Power source | DC 6V, 300mA              |
| Mounted type | Wall surface mounted type |
| Wiring       | 2 wires                   |
| Dimension    | 98 X 215 X 38(mm)         |
| Distance     | 100m(0,65Φ)               |


### System Diagram



### System Diagram



### System Diagram



# INTERCOM & WIRELESS INTERCOM

• Factory • Office • Hospital



## INTERCOM (Plug in Play)

### CM-810 / 800S




CM-810

CM-800S

- Calling ID display on FND display
- Adjustable sound level
- Expendable up to 10 pcs
- Adjustable sound level depending on its environments
- Enabling long communication through PTT

|              |                       |
|--------------|-----------------------|
| Power source | DC 12V 250mA (CM-810) |
| Wiring       | 2 wires +n            |
| Dimension    | 183 X 169 X 41(mm)    |

### System Diagram




### CM-810M




- Calling ID display on FND display
- Adjustable sound level
- Expendable up to 10 pcs
- Adjustable sound level depending on its environments
- Enabling long communication through PTT

|              |                       |
|--------------|-----------------------|
| Power source | DC 12V 250mA (1 unit) |
| Wiring       | 3 wires + n           |
| Dimension    | 183 X 169 X 41(mm)    |

### System Diagram



### CM-801 / 800




CM-801

CM-800

- Enabling long communication through PTT function
- Calling to household
- Indicating in-use status

|              |                       |
|--------------|-----------------------|
| Power source | DC 12V 250mA (CM-801) |
| Wiring       | 2 wires +n            |
| Dimension    | 183 X 169 X 41(mm)    |

### System Diagram



## POWER INTERCOM

### PI-30LN / 20LN / 10LN



- Max 30 / Group (5 circuit 1 group) or broadcasting
- Talk function
- Volume or call sound level adjustment
- Lamp-off upon receiving call

|              |                        |
|--------------|------------------------|
| Power source | AC 100 ~ 240V, 50/60Hz |
| Wiring       | Individual 2 wires     |
| Dimension    | 313 X 228 X 98(mm)     |

## CENTRAL SWITCH BOARD

### CLS-10



Unit

TP-K



- Guard call and Talk
- Connectable with CAV-40Q, CAV-35N, CAV-70P etc.

|              |                              |
|--------------|------------------------------|
| Power source | AC 100V, 110V, 220V, 50/60Hz |
| Wiring       | 2 wires (Star)               |
| Dimension    | 290 X 265 X 76(mm)           |

## WIRELESS INTERCOM

### WI-2B



- High Audio quality adopted PLL function (Phase Locked Loop) • No cross of wires
- Calling to household • Indicating in-use status
- Available to install anywhere with AC outlet
- Enabling long communication through PTT (priority call function) • Adjustable sound level

|              |                                    |
|--------------|------------------------------------|
| Power source | AC 100 / 110 / 220 / 230V, 50/60Hz |
| Wiring       | Wireless                           |
| Dimension    | WI-2B : 144 X 142 X 47(mm)         |

## WIRELESS INTERCOM

### WI-3SN




- High Audio quality adopted PLL function (Phase Locked Loop) • No cross of wires
- Calling to household • Indicating in-use status
- Available to install anywhere with AC outlet
- Enabling long communication through PTT (priority call function) • Adjustable sound level

|              |                                    |
|--------------|------------------------------------|
| Power source | AC 100 / 110 / 220 / 230V, 50/60Hz |
| Wiring       | Wireless                           |
| Dimension    | WI-3SN : 186 X 133 X 44(mm)        |




# NURSE CALL SYSTEM

• Hospital



## Bed Head Console Unit & Sub Station & Digital Master Station

### System Diagram



### JNS-9900



- Nurse Call • Emergency call
- Paging • Reading light

|              |                      |
|--------------|----------------------|
| Power source | from JNS-PSM         |
| Wiring       | 4 wires              |
| Dimension    | 1350 X 261 X 129(mm) |

### JNS-3000



- Nurse Call • Emergency call
- Paging

|              |                    |
|--------------|--------------------|
| Power source | from JNS-PSM       |
| Wiring       | 4 wires            |
| Dimension    | 880 X 198 X 59(mm) |

### JNS-70MN



### JNS-PSM



- JNS-70MN Main receiver console controls the nurse-call system
- JNS-PSM

|              | JNS-70MN               | JNS-PSM               |
|--------------|------------------------|-----------------------|
| Power source | from JNS-PSM           | AC 110V~220V, 50/60Hz |
| Wiring       | 4 wires                | 4 wires               |
| Dimension    | 240 X 270 X 13(40)(mm) | .                     |

### JNS-1000



- Nurse Call • Emergency call
- Paging • Talk to Nurse Station

### JNS -101/102/1050M (S)



- Nurse Call • Emergency call
- Paging • Talk to Nurse Station

|              | JNS-1000           | JNS -101/102/1050M (S) |
|--------------|--------------------|------------------------|
| Power source | from JNS-PSM       | from JNS-PSM           |
| Wiring       | 4 wires            | 4 wires                |
| Dimension    | 530 X 117 X 62(mm) | 195 X 117 X 62(mm)     |

### JNS-6KO



### FS-600



### AS-100



- JNS-6KO Call System in the Operation room/Flush Mount Type
- FS-600 Operation Room Installation / Foot Switch/Flush Mount Type
- AS-100 Operation Room Installation / Arm Switch/Flush Mount Type

|           | DR-6KO             | FS-600                 | AS-100                 |
|-----------|--------------------|------------------------|------------------------|
| Wiring    | 9 wires            | 6 wires                | 3 wires                |
| Dimension | 370 X 117 X 45(mm) | 573 X 117 X 16(66)(mm) | 195 X 117 X 16(66)(mm) |

### JNS-36



### CC-200



### ES-420



### PS-100



- JNS-36 Handset / Hands-free/Emergency Call Check/Call Signal Indication(Sickroom)/Paging
- CC-200 Emergency Call Cord/Fixing clip on the bed
- ES-420 Emergency Switch/Waterproof
- PS-100 Pillow Speaker/Remote control of ON/OFF (2 Lamps)

|              | JNS-36                | CC-200  | ES-420             | PS-100            |
|--------------|-----------------------|---------|--------------------|-------------------|
| Power source | AC 110V~220V, 50/60Hz | .       | .                  | .                 |
| Wiring       | 3 wires (star)        | 2 wires | 2 wires            | 4 wires           |
| Dimension    | 360 X 232 X 105(mm)   | .       | 120 X 120 X 10(mm) | 55 X 171 X 20(mm) |

### CL-302C



### ES-400



### PB-500











- CL-302C Corridor Light/Colors selectable(2 Color)
- ES-400 Emergency Switch(restroom)/Push Button Type/Waterproof/Flush Mount Type
- PB-500 Presence Switch/Flush Mount Type

|           | CL -302C        | ES -400          | PB -500           |
|-----------|-----------------|------------------|-------------------|
| Wiring    | 3 wires         | 2 wires          | 2 wires           |
| Dimension | 94 X 94 X 2(mm) | 71 X 116 X 9(mm) | 55 X 171 X 20(mm) |


# CAMERA

- In door & Out door
- Monitoring and talk with a visitor



| LOBBY PHONE   |   | Image Sensor | Wiring Type  | Min.Illumination             | Dimension(mm)  | Installation & Function  |
|---|---|--------------|--|------------------------------|--|--|
| <div><div>NEW</div><div><br/>Crystal Window<br/>Video Door Phone</div></div> | <div>DRC-700S</div> <div><div>Rain Shield</div></div>   | Color CCD    | 8 wires(UTP)<br>All-Lan<br>Flush Mounted type<br>•<br>Wall surface mounted type                            | 0 Lux<br>(300mm from Camera) | 240 x 270 x 13[40](mm)<br>•<br>236 x 256 x 80(mm)<br>(Flush Box Dimension) | <b>Out door</b><br>Monitoring and talk with a visitor<br>• Door lock release • RFID card<br>• Calling and talking with household & Guard station   |
|   | <div>DRC-700LC / RF, 700LGC</div> <div><div><div>NEW</div><div><br/>Crystal Window<br/>Video Door Phone</div></div><div><div>Rain Shield</div></div></div> | Color CCD    | 12 wires (Home Automation)/<br>8 wires (Gate View)<br>Flush Mounted type<br>•<br>Wall surface mounted type | 0 Lux<br>(300mm from Camera) | 240 x 270 x 13[40](mm)<br>•<br>236 x 256 x 80(mm)<br>(Flush Box Dimension) | <b>Out door</b><br>Monitoring and talk with a visitor<br>• Door lock release • Each pin setting per a house<br>• Calling and talking with household & Guard station<br>• RF card (Option)  |
| <div><div>NEW</div></div>   | <div>DRC-900LVC<br/>(Vandal Proof)</div> <div><div>Rain Shield</div></div>  | Color C-MOS  | 8 wires (Gate View)<br>Flush Mounted type<br>•<br>Wall surface mounted type                                | 0 Lux<br>(300mm from Camera) | 130 x 240 x 13[40](mm)   | <b>Out door</b><br>• Separate wires for Guard connection<br>• Alluminum Diecasting<br>• Monitoring and talk with a visitor<br>• Door lock release<br>• Calling and talking with household & Guard station<br>• RF card (Option)  |
|   | <div>DRC-GAC</div> <div></div>   | Color CCD    | UTP(CAT. 5e)<br>•<br>Flush Mounted type  | 0 Lux<br>(300mm from Camera) | 123 X 314 X 50(mm)<br>•<br>236 x 400 x 100(mm)<br>(Flush Box Dimension)    | <b>Out door</b><br>Monitoring and talk with a visitor<br>• <b>Max. 4 Lobby Panels connectable</b><br>• <b>House call by household number</b><br>• Door lock release • Each pin setting per a house<br>• Calling and talking with household & Guard station<br>• RF card (Option) |
|   | <div>DRC-481LC / RF</div> <div></div>  | Color CCD    | 12 wires (Home Automation)<br>8 wires (Gate View)<br>Flush Mounted type                                    | 0 Lux<br>(300mm from Camera) | 230 x 260 x 9[74](mm)<br>•<br>236 x 400 x 100(mm)<br>(Flush Box Dimension) | <b>Out door</b><br>Monitoring and talk with a visitor<br>• Door lock release • Each pin setting per a house<br>• Calling and talking with household & Guard station<br>• RF card (Option)  |

## DOOR CAMERA

|  | Image Sensor | Wiring Type | Min.Illumination             | Dimension(mm)          | Installation & Function  |
|--|--------------|-------------|------------------------------|------------------------|--|
|  <b>DRC-4FC</b><br>                                  | Color C-MOS  | 50m (Φ0.65) | 0 Lux<br>(300mm from Camera) | 94 x 136 x 34(mm)      | In door & Out door<br>• Monitoring and talk with a visitor<br>• Door lock release                |
|  <b>DRC-4QC</b><br>                                  | Color C-MOS  | 50m (Φ0.65) | 0 Lux<br>(300mm from Camera) | 94 x 136 x 34(mm)      | In door<br>• Monitoring and talk with a visitor<br>• Door lock release                           |
|  <b>DRC-4CGN</b><br>                                 | Color C-MOS  | 50m (Φ0.65) | 0 Lux<br>(300mm from Camera) | 87 x 120 x 18(mm)      | In door & Out door<br>• Monitoring and talk with a visitor<br>• Door lock release                |
|  <b>DRC-4CPN</b><br>                                 | Color C-MOS  | 50m (Φ0.65) | 0 Lux<br>(300mm from Camera) | 50 x 118 x 16(mm)      | In door & Out door<br>• Monitoring and talk with a visitor<br>• Door lock release                |
|  <b>DRC-4MC</b><br>                                | Color C-MOS  | 50m (Φ0.65) | 0 Lux<br>(300mm from Camera) | 96 x 155 x 32.5(mm)    | In door & Out door<br>• LED light<br>• Monitoring and talk with a visitor<br>• Door lock release |
|  <b>DRC-40CIC</b><br>                            | Color C-MOS  | 50m (Φ0.65) | 0 Lux<br>(300mm from Camera) | 92 x 172 x 16 [48](mm) | In door<br>• LED light<br>• Monitoring and talk with a visitor                                   |
|  <b>DRC-4CH</b><br>                              | Color CCD    | 50m (Φ0.65) | 0 Lux<br>(300mm from Camera) | 116 x 169 x 42(mm)     | In door & Out door<br>• Monitoring and talk with a visitor<br>• Door lock release                |
|  <b>DRC-40CK</b><br>                             | Color C-MOS  | 50m (Φ0.65) | 0 Lux<br>(300mm from Camera) | 93 x 135 x 30(mm)      | In door & Out door<br>• Monitoring and talk with a visitor<br>• Door lock release                |
|  <b>DRC-40CS</b><br>                             | Color CCD    | 50m (Φ0.65) | 0 Lux<br>(300mm from Camera) | 94 x 136 x 34(mm)      | In door & Out door<br>• Monitoring and talk with a visitor<br>• Door lock release                |
|  <b>DRC-4DC</b><br>                              | Color C-MOS  | 50m (Φ0.65) | 0 Lux<br>(300mm from Camera) | 65 x 162 x 22.5(mm)    | In door & Out door<br>• Monitoring and talk with a visitor<br>• Door lock release                |
|  <b>DRC-nAC2</b><br>(n: 2,4,6,8,10,12,14,16)<br> | Color CCD    | 50m (Φ0.65) | 0 Lux<br>(300mm from Camera) | 123 x 316 x 16[48](mm) | Out door<br>• Monitoring and talk with a visitor<br>• Door lock release                          |



# SMART SECURITY SYSTEM

COMMAX security working around the clock for your peace of mind.

- IR BULLET CAMERA • BOX CAMERA • SPEED DOME CAMERA
- DOME CAMERA • STAND ALONE DVR • PC BASE DVR
- LCD MONITOR • ACCESSORY • SENSOR



## IR BULLET CAMERA

### CIR-700M50 / CIR-700M30



|                          |   |
|--------------------------|---|
| Image sensor             | 1/3" Sony 960H Ex-view HAD II CCD       |
| Effective pixels         | NTSC: 976(H)x494(V), PAL: 976(H)x582(V) |
| H. Resolution            | Effio DSP 700TV Lines                   |
| Min. illumination        | 0 Lux                                   |
| Lens                     | 2.8-12mm Varifocal DC Auto Iris lens    |
| Back light compensation  | Auto                                    |
| Day/Night conversion     | Auto                                    |
| White balance            | ATW/ PUSH/ Push Lock/ Manual (OSD)      |
| LED                      | Premium Hyper LED                       |
| Power source             | 12VDC, 12VDC/24VAC                      |
| Power consumption        | 12VDC/120mA(IR Off), 12VDC/340mA(IR On) |
| Operating Temp./Humidity | -10°C ~ +50°C / within 90% RH           |

### CIR-200S55 / CIR-100S55



|                          |  |
|--------------------------|--|
| Image sensor             | 1/3" Sony Super HAD II CCD             |
| Effective pixels         | NTSC: 768(H)x494(V) PAL: 510(H)x492(V) |
| H. Resolution            | 540TV Lines / 420TV Lines              |
| Min. illumination        | 0.1 Lux at F1.2 / 0.3 Lux at F1.2      |
| Lens                     | 6mm Fixed Lens                         |
| Back light compensation  | Auto                                   |
| Day/Night conversion     | Auto                                   |
| White balance            | ATW                                    |
| IR LED Quantity          | 55EA                                   |
| Power source             | DC 12V(±10%)                           |
| Power consumption        | IR OFF : 120mA(MAX) / IR ON : 550mA    |
| Operating Temp./Humidity | -10°C ~ +50°C / 30% ~ 80% RH           |

### CIR-200SV45 / CIR-100SV45



|                          |  |
|--------------------------|--|
| Image sensor             | 1/3" Sony Super HAD II CCD             |
| Effective pixels         | NTSC: 768(H)x494(V) PAL: 510(H)x492(V) |
| H. Resolution            | 540TV Lines / 420TV Lines              |
| Min. illumination        | 0.1 Lux at F1.2 / 0.3 Lux at F1.2      |
| Lens                     | 4~9mm DC Auto Iris Varifocal Lens      |
| Back light compensation  | Auto                                   |
| Day/Night conversion     | Auto                                   |
| White balance            | ATW                                    |
| IR LED Quantity          | 45EA                                   |
| Power source             | DC 12V(±10%)                           |
| Power consumption        | IR OFF : 120mA(MAX) / IR ON : 450mA    |
| Operating Temp./Humidity | -10°C ~ +50°C / 30% ~ 80% RH           |

### CIR-200S24 / CIR-100S24



|                          |  |
|--------------------------|--|
| Image sensor             | 1/3" Sony Super HAD II CCD             |
| Effective pixels         | NTSC: 768(H)x494(V) PAL: 510(H)x492(V) |
| H. Resolution            | 540TV Lines / 420TV Lines              |
| Min. illumination        | 0.1 Lux at F1.2 / 0.3 Lux at F1.2      |
| Lens                     | 4.3mm Fixed Lens                       |
| Back light compensation  | Auto                                   |
| Day/Night conversion     | Auto                                   |
| White balance            | ATW                                    |
| IR LED Quantity          | 24EA                                   |
| Power source             | DC 12V(±10%)                           |
| Power consumption        | IR OFF : 120mA(MAX) / IR ON : 350mA    |
| Operating Temp./Humidity | -10°C ~ +50°C / 30% ~ 80% RH           |

### CIR-417NH



|                          |   |
|--------------------------|---|
| Image sensor             | 1/3" Sony Super HAD II CCD              |
| Effective pixels         | NTSC: 768(H)x494(V), PAL: 752(H)x582(V) |
| H. Resolution            | 560TV Lines                             |
| Min. illumination        | 0 Lux                                   |
| Lens                     | 4~9mm Varifocal DC Iris Lens            |
| Back light compensation  | On / Off (with DIP SW)                  |
| Day/Night conversion     | Auto                                    |
| White balance            | ATW                                     |
| IR LED Quantity          | 36EA                                    |
| Power source             | DC 12V(±10%)                            |
| Power consumption        | IR OFF : 120mA(MAX) / IR ON : 350mA     |
| Operating Temp./Humidity | -10°C ~ +50°C / within 90% RH           |

### CIR-416NH



|                          |   |
|--------------------------|---|
| Image sensor             | 1/3" Sony Super HAD II CCD                  |
| Effective pixels         | NTSC: 768(H)x494(V)                         |
| H. Resolution            | 500(Day)/TV Lines / 560(Night)TV Lines      |
| Min. illumination        | 0 Lux                                       |
| Lens                     | 4~9mm Varifocal Manual Iris Lens (Standard) |
| Back light compensation  | Auto  |
| Day/Night conversion     | Auto  |
| White balance            | ATW   |
| IR LED Quantity          | 20EA  |
| Power source             | DC 12V(±10%)                                |
| Power consumption        | IR OFF : 120mA(MAX) / IR ON : 340mA         |
| Operating Temp./Humidity | -10°C ~ +50°C / 90% RH                      |

## BOX CAMERA

### CIR-27AT24



|                          |                                     |
|--------------------------|-------------------------------------|
| Image sensor             | 1/3" Color CCD                      |
| Effective pixels         | NTSC: 510(H)x492(V)                 |
| H. Resolution            | 380TV Lines                         |
| Min. illumination        | 0 Lux (LED on)                      |
| Lens                     | 6mm Board Lens                      |
| Back light compensation  | Auto                                |
| Day/Night conversion     | Auto                                |
| White balance            | 2500°K ~ 9000°K                     |
| IR LED Quantity          | 24EA                                |
| Power source             | DC 12V(±10%)                        |
| Power consumption        | IR OFF : 120mA(MAX) / IR ON : 360mA |
| Operating Temp./Humidity | -10°C ~ +50°C / 30% ~ 80% RH        |

### CBC-700



|                          |   |
|--------------------------|---|
| Image sensor             | 1/3" Sony 960H Ex-view HAD CCD II       |
| Effective pixels         | NTSC: 976(H)x494(V), PAL: 976(H)x582(V) |
| H. Resolution            | 700TV Lines                             |
| Min. illumination        | 0.1Lux (Color) / 0.01Lux (BW)           |
| Back light compensation  | BLC/ HLC/ Off                           |
| Day/Night conversion     | Auto                                    |
| White balance            | 1800°K ~ 10500°K Auto                   |
| Power source             | DC 12V(±10%)                            |
| Power Assumption         | 150mA/12VDC                             |
| Operating Temp./Humidity | -10°C ~ +50°C / within 90% RH           |

## SPEED DOME CAMERA

### CSP-700X36



|                          |   |
|--------------------------|---|
| Image Sensor             | 1/4" SONY Super HAD II CCD (Double Scan)    |
| Effective Pixels         | NTSC:1028(H)x508(V)/PAL:1028(H)x596(V)      |
| Horizontal Resolution    | 700TV Lines                                 |
| Zoom                     | Optical 36x, Digital 32x                    |
| Min.Illumination         | Color DSS Off: 0.5lux, BW:0.2 lux           |
| Ingress Protection       | IP66 (Outdoor Housing)                      |
| Day&Night Screen Switch  | Auto / Sens-in / Ext / Day / Night          |
| White Balance            | ATW/One-Push/Indoor/Outdoor/Manual/Auto     |
| Power Supply             | 21~28VAC 60Hz / 50Hz                        |
| Pan                      | 360° Continuous Pan/0.1° to 90°/sec.        |
| Pan Preset Speed         | 380°/sec, ± 0.1° Accuracy                   |
| Tilt / Tilt Preset Speed | 0.1° to 90°/sec, 150°/sec, ± 0.01° Accuracy |

### CSP-700X36W



|                          |   |
|--------------------------|---|
| Image Sensor             | 1/4" SONY Super HAD II CCD (Double Scan)    |
| Effective Pixels         | NTSC:1028(H)x508(V)/PAL:1028(H)x596(V)      |
| Horizontal Resolution    | 700TV Lines (Color)                         |
| Zoom                     | Optical 36x, Digital 32x                    |
| Min.Illumination         | Color : 0.5lux, BW : 0.2 lux                |
| Ingress Protection       | IP66 (Outdoor Housing)                      |
| Day&Night Screen Switch  | Auto / Sens-in / Ext / Day / Night          |
| White Balance            | ATW/One-Push/Indoor/Outdoor/Manual/Auto     |
| Power Supply             | 21~28VAC 60Hz / 50Hz                        |
| Pan                      | 360° Continuous Pan/0.1° to 90°/sec.        |
| Pan Preset Speed         | 380°/sec, ± 0.1° Accuracy                   |
| Tilt / Tilt Preset Speed | 0.1° to 90°/sec, 150°/sec, ± 0.01° Accuracy |

## DOME CAMERA

### CVD-700M20



|                          |  |
|--------------------------|--|
| Image Sensor             | 1/3" Sony 960H Ex-view HAD CCD II      |
| Effective Pixels         | NTSC:976(H)x494(V), PAL: 976(H)x582(V) |
| Horizontal Resolution    | 700TV Lines                            |
| Min.Illumination         | 0 Lux                                  |
| Lens                     | 3.3~12mm Varifocal DC Iris Lens        |
| Revising backlight       | Auto                                   |
| Day&Night Screen Switch  | Auto                                   |
| White Balance            | ATW/PUSH/Push Lock/Manual (OSD)        |
| Power Supply             | 12VDC/24VAC                            |
| Operating Temp./Humidity | -10°C ~ +50°C / within 90% RH          |

### CID-700S



|                          |  |
|--------------------------|--|
| Image Sensor             | 1/3" Sony 960H Ex-view HAD CCD II      |
| Effective Pixels         | NTSC:976(H)x494(V), PAL: 976(H)x582(V) |
| Horizontal Resolution    | 700TV Lines                            |
| Min.Illumination         | 0 Lux                                  |
| Lens                     | 3.3~12mm Varifocal DC Auto Iris lens   |
| Revising backlight       | Auto                                   |
| Day&Night Screen Switch  | Auto                                   |
| White Balance            | ATW/ PUSH/Push Lock/Manual (OSD)       |
| Power Supply             | 12VDC, 12VDC/24VAC                     |
| Operating Temp./Humidity | -10°C ~ +50°C / within 90% RH          |

### CIR-4108NH



|                          |  |
|--------------------------|--|
| Image Sensor             | 1/3" Sony 960H Double Scan CCD         |
| Effective Pixels         | NTSC:976(H)x494(V), PAL: 976(H)x582(V) |
| Horizontal Resolution    | 700TV Lines                            |
| Min.Illumination         | 0 Lux                                  |
| Lens                     | 3.3~12mm Varifocal DC Iris Lens        |
| Revising backlight       | On / Off by OSD                        |
| Day&Night Screen Switch  | Auto                                   |
| White Balance            | ATW/Push Lock Selectable by OSD        |
| IR LED Quantity          | 21EA                                   |
| Power Supply             | DC 12V / AC 24V                        |
| Power Consumption        | 260mA/12VDC, 120mA/ 24VAC              |
| Operating Temp./Humidity | -10°C ~ +50°C / within 90% RH          |

### CIR-200SD



|                          |                                     |
|--------------------------|-------------------------------------|
| Image Sensor             | 1/3" Sony Super HAD II CCD          |
| Effective Pixels         | NTSC: 768(H) x 494(V)               |
| Horizontal Resolution    | 540TV Lines                         |
| Min.Illumination         | 0.1 Lux at F1.2                     |
| Lens                     | 4.3mm Fixed Lens                    |
| Revising backlight       | Auto                                |
| Day&Night Screen Switch  | Auto                                |
| White Balance            | ATW                                 |
| IR LED quantity          | 24EA                                |
| Power Supply             | DC 12V(±10%)                        |
| Power Consumption        | IR OFF : 120mA(MAX) / IR ON : 350mA |
| Operating Temp./Humidity | -10°C ~ +50°C / 30% ~ 80% RH        |

### CIR-100SD



|                          |                                     |
|--------------------------|-------------------------------------|
| Image Sensor             | 1/3" Sony Super HAD CCD             |
| Effective Pixels         | NTSC: 510(H) x 492(V)               |
| Horizontal Resolution    | 420TV Lines                         |
| Min.Illumination         | 0.3 Lux at F1.2                     |
| Lens                     | 4.3mm Fixed Lens                    |
| Revising backlight       | Auto                                |
| Day&Night Screen Switch  | Auto                                |
| White Balance            | ATW                                 |
| IR LED quantity          | 24EA                                |
| Power Supply             | DC 12V(±10%)                        |
| Power Consumption        | IR OFF : 120mA(MAX) / IR ON : 350mA |
| Operating Temp./Humidity | -10°C ~ +50°C / 30% ~ 80% RH        |

### CID-200S



|                          |                              |
|--------------------------|------------------------------|
| Image Sensor             | 1/3" Sony Super HAD II CCD   |
| Effective Pixels         | NTSC: 768(H) x 494(V)        |
| Horizontal Resolution    | 540TV Lines                  |
| Min.Illumination         | 0.1 Lux at F1.2              |
| Lens                     | 3.6mm Fixed Lens             |
| Revising backlight       | Auto                         |
| Day&Night Screen Switch  | Auto                         |
| White Balance            | ATW                          |
| Power Supply             | DC 12V(±10%)                 |
| Power Consumption        | 120mA(MAX)                   |
| Operating Temp./Humidity | -10°C ~ +50°C / 30% ~ 80% RH |

### CID-100S



|                          |                              |
|--------------------------|------------------------------|
| Image Sensor             | 1/3" Sony Super HAD CCD      |
| Effective Pixels         | NTSC: 510(H) x 492(V)        |
| Horizontal Resolution    | 380TV Lines                  |
| Min.Illumination         | 0.3 Lux at F1.2              |
| Lens                     | 3.6mm Fixed Lens             |
| Revising backlight       | Auto                         |
| Day&Night Screen Switch  | Auto                         |
| White Balance            | ATW                          |
| Power Supply             | DC 12V (±10%)                |
| Power Consumption        | 120mA (MAX)                  |
| Operating Temp./Humidity | -10°C ~ +50°C / 30% ~ 80% RH |

### CDC-27AT



|                          |                                     |
|--------------------------|-------------------------------------|
| Image Sensor             | CCD                                 |
| Effective Pixels         | NTSC: 768(H) x 494(V)               |
| Horizontal Resolution    | 380TV Lines                         |
| Min.Illumination         | 0.3 Lux at F1.2                     |
| Lens                     | 3.6mm Fixed Lens                    |
| Revising backlight       | Auto                                |
| White Balance            | ATW                                 |
| Power Supply             | DC 12V(±10%)                        |
| Power Consumption        | IR OFF : 120mA(MAX) / IR ON : 350mA |
| Operating Temp./Humidity | -10°C ~ +50°C / 30% ~ 80% RH        |



## STAND ALONE DVR

### CSD-40HD

**D1**



|           |                  |  |
|-----------|------------------|--|
| Video     | Input            | 4 BNC  |
|           | Output           | 1 VGA & 1 BNC (Dual Display)   |
| Audio     | Input            | 4 RCA (Line In)  |
|           | Output           | 1 RCA (Line Out)   |
| Device    | Sensor input     | 4 TTL  |
|           | Alarm output     | 2 TTL  |
| Recording | Compression      | H.264 Codec  |
|           | Speed/Resolution | 120fps@CIF(NTSC)<br>60fps@Half D1(NTSC)<br>30fps@D1(NTSC)                |
| Saving    | Recording Mode   | Time, Event, Time & Event, Panic   |
|           | Backup           | 2 x SATA HDD   |
| Control   | Backup           | External HDD(USB), External USB Memory                                   |
|           | Control          | Front Panel Button, USB Mouse, IR Remote Controller, Joystick Controller |
| Power     |                  | DC 12V, 3.33A (40W)  |

### CSD-80HD

**D1**



|           |                  |  |
|-----------|------------------|--|
| Video     | Input            | 8 BNC  |
|           | Output           | 1 VGA & 1 BNC (Dual Display)   |
| Audio     | Input            | 8 RCA (Line In)  |
|           | Output           | 1 RCA (Line Out)   |
| Device    | Sensor input     | 4 TTL  |
|           | Alarm output     | 2 TTL  |
| Recording | Compression      | H.264 Codec  |
|           | Speed/Resolution | 240fps@CIF(NTSC)<br>120fps@Half D1(NTSC)<br>60fps@D1(NTSC)               |
| Saving    | Recording Mode   | Time, Event, Time & Event, Panic   |
|           | Backup           | 2 x SATA HDD   |
| Control   | Backup           | External HDD(USB), External USB Memory                                   |
|           | Control          | Front Panel Button, USB Mouse, IR Remote Controller, Joystick Controller |
| Power     |                  | DC 12V, 6.67A (80W)  |

### CSD-160HD

**D1**



|           |                  |  |
|-----------|------------------|--|
| Video     | Input            | 16 BNC   |
|           | Output           | 1 VGA & 1 BNC (Dual Display)   |
| Audio     | Input            | 8 RCA (Line In)  |
|           | Output           | 1 RCA (Line Out)   |
| Device    | Sensor input     | 4 TTL  |
|           | Alarm output     | 2 TTL  |
| Recording | Compression      | H.264 Codec  |
|           | Speed/Resolution | 480fps@CIF(NTSC)<br>240fps@Half D1(NTSC)<br>120fps@D1(NTSC)              |
| Saving    | Recording Mode   | Time, Event, Time & Event, Panic   |
|           | Backup           | 2 x SATA HDD   |
| Control   | Backup           | External HDD(USB), External USB Memory                                   |
|           | Control          | Front Panel Button, USB Mouse, IR Remote Controller, Joystick Controller |
| Power     |                  | DC 12V, 6.67A (80W)  |

### CSD-40HN



|           |                  |  |
|-----------|------------------|--|
| Video     | Input            | 4 BNC  |
|           | Output           | 1 VGA & 1 BNC Main   |
| Audio     | Input            | 1 RCA (Line In)  |
|           | Output           | 1 RCA (Line Out)   |
| Device    | Sensor input     | 4 TTL  |
|           | Alarm output     | 2 TTL  |
| Recording | Compression      | H.264 Codec  |
|           | Speed/Resolution | 120fps@CIF(NTSC)<br>60fps@Half D1(NTSC)<br>30fps@D1(NTSC)                |
| Saving    | Recording Mode   | Time-lapse, Event, Time & Event  |
|           | Backup           | 1 x SATA HDD   |
| Control   | Backup           | External USB Memory  |
|           | Control          | Front Panel Button, USB Mouse, IR Remote Controller, Joystick Controller |
| Power     |                  | DC 12V, 3.33A (40W)  |

### CSD-80HN



|           |                  |  |
|-----------|------------------|--|
| Video     | Input            | 8 BNC  |
|           | Output           | 1 VGA & 1 BNC Main, 1 Spot Output  |
| Audio     | Input            | 4 RCA (Line In)  |
|           | Output           | 1 RCA (Line Out)   |
| Device    | Sensor input     | 8 TTL  |
|           | Alarm output     | 2 Relay + 2 TTL  |
| Recording | Compression      | H.264 Codec  |
|           | Speed/Resolution | 120fps@CIF(NTSC) 60fps@Half D1(NTSC)<br>30fps@D1(NTSC)                   |
| Saving    | Recording Mode   | Time-lapse, Event, Time & Event, Emergency(Panic)                        |
|           | Backup           | 3 x SATA HDD & 1 x SATA ODD (or max 4 SATA HDD without ODD)              |
| Control   | Backup           | CD&DVD-RW, External HDD(USB), External USB Memory                        |
|           | Control          | Front Panel Button, USB Mouse, IR Remote Controller, Joystick Controller |
| Power     |                  | DC 12V, 6.67A (80W)  |

### CSD-160HN



|           |                  |  |
|-----------|------------------|--|
| Video     | Input            | 16 BNC   |
|           | Output           | 1 VGA & 1 BNC Main, 1 Spot Output  |
| Audio     | Input            | 4 RCA (Line In)  |
|           | Output           | 1 RCA (Line Out)   |
| Device    | Sensor input     | 16 TTL   |
|           | Alarm output     | 2 Relay + 2 TTL  |
| Recording | Compression      | H.264 Codec  |
|           | Speed/Resolution | 240fps@CIF(NTSC) 120fps@Half D1(NTSC)<br>60fps@D1(NTSC)                  |
| Saving    | Recording Mode   | Time-lapse, Event, Time & Event, Emergency(Panic)                        |
|           | Backup           | 3 x SATA HDD & 1 x SATA ODD (or max 4 SATA HDD without ODD)              |
| Control   | Backup           | CD & DVD-RW, External HDD(USB), External USB Memory                      |
|           | Control          | Front Panel Button, USB Mouse, IR Remote Controller, Joystick Controller |
| Power     |                  | DC 12V, 6.67A (80W)  |

## PC BASE DVR

### CVR-4120W



|                  |            |  |
|------------------|------------|--|
| Video input      |            | 16CH (BNC)   |
| Video output     |            | PC Monitor (VGA)-1Ch, TV Out(BNC)-1Ch                      |
| Compression      |            | H.264  |
| Rec. speed       | FPS        | 120 Frame/Sec  |
|                  | Speed      | 720 x 480, 720 x 240, 360 x 240                            |
| Live speed       | Resolution | 480 Frame/Sec  |
|                  | Speed      | 8 / 5  |
| Sensor in/output |            | 16 / 1 (RCA)   |
| Audio in/output  |            | WEB, Client, Secuman (CMS), PDA, Smart Phone (Android 2.2) |
| Network          |            | Program  |
| Dimension        |            | 437(W) x 174(H) x 455(D)mm                                 |

### CVR-4120W(U)



|                  |            |  |
|------------------|------------|--|
| Video input      |            | 16CH (BNC)   |
| Video output     |            | PC Monitor (VGA)-1Ch, TV Out (BNC)-1Ch                     |
| Compression      |            | H.264  |
| Rec. speed       | FPS        | 120 Frame/Sec  |
|                  | Speed      | 720 x 480, 720 x 240, 360 x 240                            |
| Live speed       | Resolution | 480 Frame/Sec  |
|                  | Speed      | 8 / 5  |
| Sensor in/output |            | 16 / 1 (RCA)   |
| Audio in/output  |            | WEB, Client, Secuman (CMS), PDA, Smart Phone (Android 2.2) |
| Network          |            | Program  |
| Dimension        |            | 437(W) x 174(H) x 455(D)mm                                 |

### CVR-4480W



|                  |            |  |
|------------------|------------|--|
| Video input      |            | 6CH (BNC), 4CH UTP   |
| Video output     |            | PC Monitor (VGA)-1Ch, TV Out (BNC)-1Ch                     |
| Compression      |            | H.264  |
| Rec. speed       | FPS        | 480 Frame/Sec  |
|                  | Speed      | 720 x 480, 720 x 240, 360 x 240                            |
| Live speed       | Resolution | 480 Frame/Sec  |
|                  | Speed      | 8 / 5  |
| Sensor in/output |            | 16 / 1 (RCA)   |
| Audio in/output  |            | WEB, Client, Secuman (CMS), PDA, Smart Phone (Android 2.2) |
| Network          |            | Program  |
| Dimension        |            | 437(W) x 174(H) x 455(D)mm                                 |





## LCD MONITOR

### CVR-4480W(U)



|                  |  |
|------------------|--|
| Video input      | 16CH (BNC), 4CH UTP  |
| Video output     | PC Monitor (VGA)-1Ch, TV Out (BNC)-1Ch                     |
| Compression      | H.264  |
| Rec. speed       | FPS  |
|                  | Speed  |
| Live speed       | 480 Frame/Sec  |
| Sensor in/output | 720 × 480, 720 × 240, 360 × 240                            |
| Speed            | 480 Frame/Sec  |
| Resolution       | 8 / 5  |
| Audio in/output  | 16 / 1 (RCA)   |
| Network          | WEB, Client, Secuman (CMS), PDA, Smart Phone (Android 2.2) |
| Program          |  |
| Dimension        | 437(W) × 174(H) × 455(D)mm                                 |

### CVR-4120W(U)



|                  |  |
|------------------|--|
| Video input      | 32CH (BNC)   |
| Video output     | PC Monitor (VGA)-1Ch, TV Out (BNC)-1Ch                     |
| Compression      | H.264  |
| Rec. speed       | FPS  |
|                  | Speed  |
| Live speed       | 480 Frame/Sec  |
| Sensor in/output | 720 × 480, 720 × 240, 360 × 240                            |
| Speed            | 960 Frame/Sec  |
| Resolution       | 8 / 5  |
| Audio in/output  | 16 / 1 (RCA)   |
| Network          | WEB, Client, Secuman (CMS), PDA, Smart Phone (Android 2.2) |
| Program          |  |
| Dimension        | 437(W) × 174(H) × 455(D)mm                                 |

### CLM-190W



19" TFT LCD Monitor / Clear image quality  
Contrast range 1,000 : 1 / Response speed 5ms

## ACCESSORY

### HOUSING

#### COH-200 / COH-200FH | CIH-100



|             |   |                          |
|-------------|---|--------------------------|
| Application | COH-200(Outdoor)   COH-200FH (Fan&Heater Outdoor) | CIH-100 (Indoor)         |
| Material    | Aluminum(Front & Back side ABS)                   | Aluminum                 |
| Color       | Ivory   Ivory                                     | Ivory                    |
| Dimension   | 146(W) × 102(H) × 422(D)mm                        | 99(W) × 83(H) × 323(D)mm |
| Weight      | 1.3Kg   1.5Kg                                     | 780g                     |

### BRACKET



|                           |                   |                   |                   |                   |
|---------------------------|-------------------|-------------------|-------------------|-------------------|
| MODEL                     | CB-S2             | CB-S3             | CB-S4             | CB-J1             |
| Material                  | Aluminum          | Aluminum          | Aluminum          | Aluminum          |
| Height                    | 100mm             | 100mm             | 250~350mm         | 250~350mm         |
| Bottom diameter           | 68(D)             | 68(D)             | 90(D)             | 90(D)             |
| Type                      | 1                 | 1                 | 1                 | J                 |
| Clamping screw            | 1/4" 20-UNC       | 1/4" 20-UNC       | 1/4" 20-UNC       | 1/4" 20-UNC       |
| Left & Right moving angle | 360°              | 360°              | 360°              | 360°              |
| Up & Down moving angle    | 690°              | 690°              | 690°              | 690°              |
| Loading capacity          | 2.5Kg             | 2.5Kg             | 2.5Kg             | 2.5Kg             |
| Color                     | Bright gold color | Bright gold color | Bright gold color | Bright gold color |
| Dimension                 | 68(D)/100(H)mm    | 68(D)/150(H)mm    | 90(D)/250(H)mm    | 90/180/140mm      |
| Weight                    | 225g              | 230g              | 405g              | 405g              |

## SENSOR

### CIS-30M



### CIS-10M



### CPS-100D



### CPS-200P



### MS-10



|                  |                               |                               |                                   |                                   |                   |
|------------------|-------------------------------|-------------------------------|-----------------------------------|-----------------------------------|-------------------|
| Protection Range | Indoor : 60m<br>Outdoor : 30m | Indoor : 30m<br>Outdoor : 10m | Wide angle 96°<br>Standard 12~15m | Wide angle 84°<br>Standard 12~15m | 25~55mm           |
| Power Source     | DC 10.8~25V                   | DC 10.8~25V                   | DC 8~18V                          | DC 8~14V                          | 0.5A              |
| Dimension        | 73 X 177 X 84 (mm)            | 73 X 177 X 84 (mm)            | 131 X 60 (mm)                     | 55 X 13 X 12 (mm)                 | 65 X 14 X 14 (mm) |
| Response time    | 50~700msec                    | 50~700msec                    |                                   |                                   |                   |
| Mounting Site    | Outdoor, Indoor               | Outdoor, Indoor               | Indoor                            | Indoor                            | Inside of door    |
| IP Rating        | IP 44                         | IP 44                         |                                   |                                   |                   |